DOUBLE SIDED

Hanging Double-sided Window Displays

High vibrance Super-Slim **Dual Sided Display for** Windows with Integrated Ceiling Mounting Solution







Double Sided Window Display

Grab the attention of onlookers with the outward facing, sunlight readable screen. Once your customers are inside the building you can then use the inward facing display to reinforce your message further

Plug and Play

The Double Sided Hanging Displays come with a built in HD Android media player, allowing you to update them using a USB memory stick. Load your pictures and videos onto a USB memory stick then insert it into the display, which will copy the files into its internal flash memory. Once you remove the memory stick the screen will then start playing the pictures and videos in a continuous loop.

700cd/m² brightness

Brightness is paramount when using outward facing screens, these displays use commercial grade high brightness panels (700cd/m²); more than twice the brightness of a standard home TV to allow easy readability in window displays.

- Optional Network Upgrade
- Ultra Resistant to Blackening
- Integrated Ceiling Mount
- Super Slim Design
- Commercial Grade Panel and Components
- Integrated Speakers



DOUBLE SIDED WINDOW DISPLAYS

Specification

| Part number | Diagonal | Resolution | Display area | cd/m² | Overall size | Weight |
|-------------|----------|------------|--------------|---------|-------------------|--------|
| CDS-430-DS | 43" | 1920x1080 | 943.2x531.4 | 700/700 | 1178.3x634.6x21.6 | 16.9kg |
| CDS-550-DS | 55" | 1920x1080 | 1209.6x680.4 | 700/700 | 1479.4x817.2x21.6 | 26.6kg |

Panel

| Aspect Ratio | Colour | Viewing angle | Blackening Defect Free |
|--------------|--------|---------------|-------------------------------|
| 16:9 | 16.7M | 178° | Up to 110°C (230°F) |

AV Inputs

| Video | Audio | Speaker type |
|-----------|----------------------|--------------|
| HDMI, VGA | Audio Socket (3.5mm) | 2W, 5Ω (x2) |

Environmental

| Operating temp | Storage temp | Operating Humidity | Storage Humidity |
|----------------|---------------|---------------------------|------------------|
| 0°C to 40°C | -20°C to 60°C | 10% to 90% | 0% to 95% |
| | | | |

Computer / media player

| Media formats Video (MPG, AVI, MP4, RM, RMVB, TS), Audio (MP3, WMA), Image (JPG, GIF, BMP, PNG) | Media resolution 1920x1080/1080x1920 | CPU Quad-Core ARM Cortex A17, 1.6GHz | GPU Quad-Core ARM Mali- T760 MP4 @600Mhz |
|---|---|---|---|
| RAM DDR3 2GB | Internal storage 8GB NAND | USB USB2.0 HOST (x2) | LAN 100M/1000M Ethernet (Network Version Only) |
| Wi-Fi 802.11b/g/n (Network Version Only) | OS Android 5.1.1 | Graphic engine OpenGL ES 1.1/2.0/3.0/3.1, OpenCL 1.1, Renderscript, Direct3D 11.1 | |

NOTE - To achieve different content on each side, the network upgrade with CMS is required



DOUBLE SIDED WINDOW DISPLAYS

Example applications













Need any additional information?

If you need any assistance with pricing information, technical support or require any additional information our team would be more than happy to assist.



CONTACT US:

Crystal Display Systems Ltd Unit 6 M2M Park, Fort Bridgewood, Maidstone Road, Rochester, Kent ME1 3DQ United Kingdom

T: +44 (0) 1634 791600 E: info@crystal-display.com W: www.crystal-display.com

SPECIALIST GLOBAL SUPPLIERS IN INNOVATIVE LCD DISPLAY SOLUTIONS AND DIGITAL SIGNAGE SOLUTIONS