

AR707

ARM INDUSTRIAL COMPUTER



Rockchip RK3588 processor
Rockchip RK3588J processor



Support HDMI, DP, eDP, MIPI-DSI/LVDS Outputs
Up to 7680 x 4320 @60 Hz



Support Wi-Fi/BT module



Fanless design
Wide temperature and voltage



CPU

CPU	Rockchip RK3588 processor Rockchip RK3588J processor
Total Cores	4-Cores Cortex-A76 and 4-Cores Cortex-A55
NPU	6 TOPs, support int4/int8/int16/FP16/BF16/TF32 acceleration
TDP	15 W

System

System Memory	8GB, Onboard LPDDR4/LPDDR4x, dual-channels 64
Storage	GB, Onboard eMMC 1 x M-Key M.2 (2242/2280) for SATA SSD 1 x TF Card reader Optional: TPM2.0
TPM	Yes
Watchdog Timer	Yes
Auto Power On	Set up independently every day, a week as a cycle
RTC	Lockable DC-IN, 12~24 V
Power Requirement	DC-IN, aviation connector, 54 V for PSE 200mm x 150mm x 60mm (7.87" x 5.90" x 2.36")
Dimensions	Metal, Grey Fanless, passive cooling Android 14
Construction	/Debian12 0°C ~60°C (32°F~140°F) @0.7m/s Air Flow
Cooling System	(RK3588) -20°C~70°C (-4°F ~158°F) @0.7m/s Air Flow
Operating System	(RK3588J) 10% ~ 90% @45°C (non-condensing)
Operating Temperature	-40°C ~80°C (-40°F~176°F) not include the package CE, FCC Class B, UKCA
Humidity	
Storage Temperature	
Certifications	

Network

Network Controller	Commercial (RK3588)	5 x Intel i210-AT Gigabit Ethernet 1 x Intel Ethernet Controller i226-V
	Industrial (RK3588J)	5 x Intel i210-IT Gigabit Ethernet 1 x Intel Ethernet Controller i226-IT
Ethernet Interface		4 x 1 GbE RJ45, support PoE+ (LAN3 ~ LAN6) 1 x 2.5 GbE RJ45, 1 x 1 GbE RJ45
Wi-Fi/BT		1 x E-Key M.2 (2230) for Wi-Fi/BT
Mobile Network		1 x B-Key M.2 (3042) for 4G, 1 x SIM Slot

Display

GPU	Mali-G610 MP4
Graphic Engine	OpenGL ES 1.1/2.0/3.2, OpenCL 1.1/1.2/2.0, Vulkan 1.1/1.2
Multi-Media	H.265/H.264/AV1/AVS2 etc. video decoder, up to 8K@60fps 8K@30fps video encoders for H.264/H.265
Display Interface	1 x HDMI (Max. 7680 x 4320 @60Hz) 1 x DP1.4 (Max. 7680 x 4320 @60Hz)
# of Displays Supported	3

I/O interface

USB	3 x USB 3.2 GEN1, 3 x USB2.0 1 x USB Type-C (USB-OTG, DP1.4)
Serial Port	4 x RS232 DB9, 2 x RS485 DB9
CAN	2 x CAN2.0 DB9
Audio	1 x 2-in-1 headset (Reserved)
Button	1 x Power on, 1 x Recovery, 1 x 5M Ground
GPIO	10pin GPIO (4 x GPI, 4 x GPO)
Antenna	2 x Wi-Fi/BT Connector, (4G Connector reserved)

Dimensions and Drawing



Order information

AR707-3588R43E6G-GIA	CPU: Rockchip RK3588 RAM: 8 GB, Onboard LPDDR4 Storage: 64 GB, Onboard eMMC Operating System: Android 14
Packing List	2 x Wi-Fi Antenna, 2 x AC Power Cable, 1 x AC Power Adapter, 1 x 54V PSE Aviation Connector Power Adaptor
Package	Carton, EPE

Optional items

Mobile Network Module	-
-----------------------	---



The terms HDMI, HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.



android



RoHS





Want More Information? Contact Us Now

Need any additional information?

If you need any assistance with pricing information, technical support or require any additional information our team would be more than happy to assist



CONTACT US:

Crystal Display Systems Ltd
Unit 6 M2M Park, Fort Bridgewood
Maidstone Road, Rochester,
Kent. ME1 3DQ

T : +44(0) 1634 791600
E : info@crystal-display.com
W : crystal-display.com

**SPECIALIST GLOBAL SUPPLIERS IN INNOVATIVE LCD
DISPLAY, TOUCH AND DIGITAL SIGNAGE SOLUTIONS**

Note: Monitor images are for marketing purposes only and you should refer to the mechanical diagrams for accurate dimensions and designs