


IceVue470 Transparent LCD Showcase Refrigerator

IV470V1 is an innovatively designed showcase refrigerator, incorporating a high definition 47" transparent LCD display. Built from the ground up as a commercial marketing solution, this complete system is available now and includes integrated Android



Display Specification			
Product		IceVue 470 Transparent LCD Refrigerator	
Model		IV470V1 (110/220)	
Size	Display	47" LG display 584.82(W) x 1039.68(H)mm	
	Cooler	690(W)x1880(H)x620(D)mm 27.16(W) x 74.01(D) x 24.41(H) inch	
	Door	680(W)x1570(H)x80(H)mm 26.77(W) x 61.81(D) x 3.15(H) inch	
Display Resolution		1,920x1,080 pixel	
Transmittance		6%	
Viewing Angle		L(80),R(80),U(80),D(80)	
	CPU	Exynos4412 1.7GHz ARM CortexA9 Quad Core	
Media B'D	o/s	Android 4.1.2	
	Memory	2G RAM	
Support Media		Video, Audio, Image	
Content Delivery		USB Memory, LAN, Wifi(option)	
LED Brightness		1top, 2sides 3 LED bar 20,000 lux	
Input	USB	2xUSB(internal), 1xUSB(external)	
Port	Network	1xLAN, Wifi(option)	
Output Port		1 HDMI, DVI, RGB, 1 Audio-Out(internal)	
Audio AMP		2x3W (* None Speaker), Audio CODEC	
Power Consumption		400W	
Power		AC 115V/60Hz, 220V/50-60HZ	
Certification		Ready for CE, UL (Q2 2014)	
ETC		2 side tempered glass aluminium door	
Cooler Specification			
Weight		N/W 98kg, G/W 106kg	
weight		14/ W 30/g, G/ W 100/g	

Cooler Specification		
Weight		N/W 98kg, G/W 106kg
Cooler Capacity		515 Liter (18.18ft³)
Cooling System		indirect cooling system
Controller		Thermostat, adjustable temp control
Compressor		1/4 HP (SAMSUNG - SK170C-L2W)
Evaporator & Refrigerant		FIN & TUBE(∮8, 9.9m) & R-134a
Fan Motor		4W x 1ea, 6P, 1600rpm, ∮150, CCW
Workable Temerature		0 ~ 10°C (32 ~ 50°F)
Pack out capacities	12oz, 16oz	7 F, 5 D, 5 SH, 6 RW Total 220
	20oz	6 F, 5 D, 4 SH, 5 RW Total 150
	24oz	6 F, 4 D, 4 SH, 5 RW Total 96
Unit per Pallet		3 units
Shipping Loads		40HQ ~ 51 units, 20HQ ~ 24 units

Crystal Display Systems Ltd

www.crystal-display.com/icevue tel:+44 (0)1634 292025